



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical travel	10	mm
Repeatability	max. 0.05	mm
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	5 Mio.	cycles
Mechanical Data		
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +85	°C
Storage temperature	-25 ... +105	°C

WL100

Applications

- Medical apparatus for tumor treatment

Features

- High life
- Minimal space requirements
- Excellent linearity up to ±0.5%
- Very good resolution, better 0.05mm

Options

- Resistance tolerance ±10%
- Independent linearity ±0.5%
- Special electrical travel
- With cable or wires available

Subject to change
without notice
State: 27-Oct-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical travel	25	mm
Repeatability	0.05	mm
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	5 Mio.	cycles
Mechanical Data		
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +85	°C
Storage temperature	-25 ... +105	°C

WL250

Applications

- Medical apparatus for tumor treatment

Features

- High life
- Excellent linearity up to ±0.25%
- Minimal space requirements
- Very good resolution, better 0.05mm

Options

- Resistance tolerance ±10%
- Independent linearity ±0.25%
- Special electrical travel
- With cables or wires available

Subject to change
without notice
State: 27-Oct-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical travel	50	mm
Repeatability	0.05	mm
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	5 Mio.	cycles
Mechanical Data		
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +85	°C
Storage temperature	-25 ... +105	°C

WL500

Applications

- Medical apparatus for tumor treatment

Features

- High life
- Excellent linearity up to ±0.25%
- Minimal space requirements
- Very good resolution, better 0.05mm

Options

- Resistance tolerance ±10%
- Independent linearity ±0.25%
- Special electrical travel
- With cable or wires available

Subject to change
without notice
State: 27-Oct-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical travel	75	mm
Repeatability	0.05	mm
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	5 Mio.	cycles
Mechanical Data		
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +85	°C
Storage temperature	-25 ... +105	°C

WL750

Applications

- Medical apparatus for tumor treatment

Features

- High life
- Excellent linearity up to ±0.25%
- Minimal space requirements
- Very good resolution, better 0.05mm

Options

- Resistance tolerance ±10%
- Independent linearity ±0.25%
- Special electrical travel
- With cables or wires available

Subject to change
without notice
State: 27-Oct-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical travel	100	mm
Repeatability	0.05	mm
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	5 Mio.	cycles
Mechanical Data		
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +85	°C
Storage temperature	-25 ... +105	°C

WL1000

Applications

- Medical apparatus for tumor treatment

Features

- High life
- Excellent linearity up to ±0.25%
- Minimal space requirements
- Very good resolution, better 0.05mm

Options

- Resistance tolerance ±10%
- Independent linearity ±0.25%
- Special electrical travel
- With cables or wires available

Subject to change
without notice
State: 27-Oct-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC